

# ARCHITECTURAL LINE IP54

Profile  Z208

Optics

<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>10°</b> Narrow Beam Frosted	<b>30°</b> Frosted	<b>90°</b> Frosted	<b>85°</b> Asymmetric Frosted
Transmission 82% 20.2 mm	Transmission 85%	Transmission 90%	Transmission 90%
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>120°</b> Cover White	<b>120°</b> Cover Frosted	<b>120°</b> Cover Flat White	<b>120°</b> Cover Flat Frosted
Transmission 75%	Transmission 92%	Transmission 70%	Transmission 87%

Module  L14-UHD

CRI  >90

End cap  Cinch

Colour temperature  
Luminous flux  
Power

\*W/module @ 24Vdc  
Module length 140 mm

Colour temperature (CRI>90)

2,400 K 2,700 K 3,000 K 4,000 K 5,000 K

Power

1W/module\*

1.5W/module\*

1.9W/module\*

2.5W/module\*

95 lm	100 lm	103 lm	114 lm	114 lm
145 lm	153 lm	158 lm	175 lm	175 lm
196 lm	206 lm	213 lm	235 lm	235 lm
246 lm	260 lm	268 lm	296 lm	296 lm

Length

(Maximum length 3,400 mm)

Protection category  IP54 CE (cinch with protection plug)

Mounting conditions

Max. ambient temperature

Fixing plates  
Mounting plates

LED FIXING PLATE ECS 0° 88166859	LED Z161 FIXING PLATE ECS 0° 88712147	LED FIXING PLATE ECS 15° 88167372	LED FIXING PLATE ECS 30° 88167373	LED FIXING PLATE ECS 45° 88167374	LED FIXING PLATE ECS 60° 88167375
LED FIXING PLATE METAL 0° 88167376	LED FIXING PLATE METAL 0° Magnetic 88167382	LED METAL ANGLE ECS 30° 88167378	LED METAL ANGLE ECS 45° 88167379	LED FIXING PLATE METAL - adjustable 88167384	LED MAGNETIC PLATE METAL - adjustable 88167385

LED driver

SWITCHABLE

- CONVERTER 35W 24V IP20 LTP-1077-V01
- CONVERTER 60W 24V IP20 LTP-1062-V0
- CONVERTER 100W 24V IP20 LTP-1063-V01
- CONVERTER 120W 24V IP67 LTP-1078-V01
- CONVERTER 200W 24V IP20 LTP-1046-V01

DIMMABLE DALI

- CONVERTER SwitchDim 35W 24V IP20 LTP-1098-V01
- CONVERTER SwitchDim 60W 24V IP20 LTP-1097-V01
- CONVERTER SwitchDim 100W 24V IP20 LTP-1096-V01
- CONVERTER SwitchDim 150W 24V IP20 LTP-1059-V01

DIMMABLE PWM

- CONVERTER PWM 40W 24V IP67 LTP-1084-V01
- CONVERTER PWM 120W 24V IP67 LTP-1048-V01

Accessories

- LED Feeder straight CINCH 3000 89601602
- LED Feeder angled CINCH 4000 89601603
- LED Feeder straight CINCH 5000 89601611
- LED Bridge straight CINCH 120 89601604
- LED Bridge straight CINCH 250 89601607
- LED Bridge angled CINCH 50 89601610
- LED Bridge CINCH direct connector 89601606
- LED PROTECTION PLUG CINCH black 88167416
- LED SEALING RING CINCH black 88167417
- STRAIN RELIEF CINCH PLUG 90° 24166456
- STRAIN RELIEF CINCH PLUG STRAIGHT 24166457

You can find further accessories at [www.lumitech.com](http://www.lumitech.com).